

# Certificate of Constancy of Performance

No. 0780-CPR-143038

In compliance with *Regulation (EU) No 305/2011 of the European Parliament and of the Council of 9 March 2011* (the Construction Products Regulation - CPR), this certificate applies to the construction products

## Fibre reinforced polymer composite lighting columns

as specified on page 2 of this certificate

produced for

**FFI Group A/S  
Fyns Flagstang Industri A/S  
Tvaervejen 3  
5580 Noerre Aaby - Denmark**

and produced in the manufacturing plant

**Plant 1**

This certificate attests that all provisions concerning the assessment and verification of constancy of performance described in Annex ZA of the harmonised standard

**EN 40-7:2002**

under system 1 for the performances set out are applied and that

**the construction products fulfil all the prescribed requirements for these performances.**

This certificate was first issued on 2015-10-23 and will remain valid as long as the test methods and/or factory production control requirements included in the harmonised standard, used to assess the performances of the declared essential characteristics, do not change, and the construction products, and the manufacturing conditions in the plant are not modified significantly, latest until 2020-10-23, unless suspended or withdrawn by the product certification body.

Nuremberg, 2015-10-23

TÜV Rheinland LGA Bautechnik GmbH  
Tillystraße 2 ▪ 90431 Nürnberg ▪ Germany  
Notified Product Certification Body 0780



*Günther Jost*  
Dipl.-Ing. (FH) Günther Jost  
Head of Certification Body

www.tuv.com



# Certificate of Constancy of Performance

No. 0780-CPR-143038

Page 2 of the Certificate of Constancy of Performance dated 2015-10-23

**Certified Construction Products:**  
**Fibre reinforced polymer composite lighting columns**

**Columns, tapered circular**

Diameter of lantern fixing 60 mm

Product	Length [m] above floor level	Diameter [mm] at floor level	Material thickness [mm] at floor level
SCL-IG-3	3.0	150	4.0 - 4.5
SCL-IG-4	4.0	150	4.0 - 4.5
SCL-IG-5	5.0	175	5.0 - 6.0
SCL-IG-6	6.0	175	5.0 - 6.0
SCL-IG-7	7.0	175	5.0 - 6.0
SCL-IG-8	8.0	195	6.0 - 7.0
SCL-IG-9	9.0	195	6.5 - 7.5
SCL-IG-10	10.0	195	6.5 - 7.5

## Further features or characteristics

- Passive safety: **class 0** acc. EN 12767
- Performance according EN 40-7
- Material: reinforced polymer composite
- Static calculation according EN 40-3-1 and EN 40-3-3 provided by the manufacturer

